

Stinger

RoadKill

FAST RINGS



RKFR6

Fits 6" and 6.5" Speakers

- Reduces panel vibration
- Increases mid-bass response
- Enhanced audio output efficiency
- Minimizes destructive wave interference
- Helps prevent front and rear wave cancellation
- Easy installation with peel & stick application
- Maximizes performance for speaker installations

RKFR

Instructions

1. Separate the RoadKill FAST Rings (RKFR) into 3 pieces.
2. Clean the back panel area of the door where RKFR piece #1 will be placed (directly behind speaker opening), then remove release liner and place it on the panel behind the speaker opening.
3. Using a razorblade, cut down RKFR piece #2 to approximately .25in/6mm. Remove release liner from the back and adhere it to the rear of the speaker, creating a mounting gasket. This will ensure an airtight seal and decouple the speaker from the door panel, preventing front/rear wave cancellation.
4. Connect and mount the speaker to the door, per normal installation procedures.
5. Clean any excess dust from the speaker and adhere RKFR piece #3 to the front face of the speaker. Now test the door panel for fitment. If needed, trim front of RKFR piece #3 so that it is making firm contact with the door panel but not crushing the RKFR. This focuses the speaker output into the listening compartment, eliminating losses and vibration between the speaker and door panel, and optimizing sound output, clarity and dynamics.



Stinger is a Power Brand of AAMP Global
support@stingerelectronics.com
stingerelectronics.com
facebook.com/stingerelectronics
© 2017 AAMP Global
Protected under the following U.S. Patent:
No. 8,739,921

RKFR6



Made in China

