

## Why SoundGate Dealers have the edge...

The technologies used in today's vehicles are as sophisticated as any laptop computer. At SoundGate we believe these new technologies are full of opportunities for mobile electronic dealers across the nation. We make it a high priority to not only research these new systems, but to understand them and their impact on the aftermarket car audio industry. Armed with this knowledge, we are well equipped to help you integrate new components into these systems with our innovative, high-performance interfaces and unparalleled technical support.

## Simple-fi™

If you experience any problems, call SoundGate Technical Support at 800-256-0808, or e-mail us at [sgtech@soundgate.com](mailto:sgtech@soundgate.com).

[www.soundgate.com](http://www.soundgate.com)

AUXMSTHD2V3



### Purpose...

The AUXMSTHD2V3 is an exciting interface that lets you add two auxiliary inputs to a number of factory radios.

SoundGate's AUXMSTR-series can be connected to many factory radios to add two auxiliary inputs (see listing below).

### Features...

The AUXMSTHD2V3 utilizes sophisticated microprocessor control, high-quality components, and advanced software design to flawlessly adapt the auxiliary input function to each vehicle's radio.

### The SoundGate AUXMSTHD2V3 works in these applications:

Acura		Honda	
1997	CL 3.0/3.2	1992-1997	Accord
1997-1999	CL 2.2/2.3	1992-1997	Civic
1992-1997	Integra	1995-1997	Odyssey
1992-1995	Legend	1992-1997	Prelude
1992-2001	NSX		
1997-1998	RL 3.5		
1996-1997	TL 2.5/3.2		
1992-1996	Vigor		

ONLY for vehicles equipped with CD-changer-ready radios.

## Be Sure To Ask Your Autosound Specialist About These Other Exciting SoundGate Products...

- Auxiliary Input Interfaces and Docking Stations which allow you to input the audio from MP3, DVD/Video, Satellite Radio, and more to OEM and aftermarket car audio systems
- High-performance Radio Replacement Interfaces for seamlessly integrating new receivers or CD players into OEM audio systems
- Competition-Grade Interfaces for adding amplifiers
- Remote Audio Control Interfaces that let you control aftermarket receivers and CD players from your factory rear seat, or steering-wheel-mounted audio controls.
- And many others!

## Simple-fi™

Copyright© 2004-2007 SoundGate®. All Rights Reserved. SoundGate® is a registered trademark of Stillwater Designs, Inc. All other trademarks are the property of their respective owners.

Rev 20070813

## Why SoundGate Dealers have the edge...

The technologies used in today's vehicles are as sophisticated as any laptop computer. At SoundGate we believe these new technologies are full of opportunities for mobile electronic dealers across the nation. We make it a high priority to not only research these new systems, but to understand them and their impact on the aftermarket car audio industry. Armed with this knowledge, we are well equipped to help you integrate new components into these systems with our innovative, high-performance interfaces and unparalleled technical support.

## Simple-fi™

If you experience any problems, call SoundGate Technical Support at 800-256-0808, or e-mail us at [sgtech@soundgate.com](mailto:sgtech@soundgate.com).

[www.soundgate.com](http://www.soundgate.com)

AUXMSTHD2V3



### Purpose...

The AUXMSTHD2V3 is an exciting interface that lets you add two auxiliary inputs to a number of factory radios.

SoundGate's AUXMSTR-series can be connected to many factory radios to add two auxiliary inputs (see listing below).

### Features...

The AUXMSTHD2V3 utilizes sophisticated microprocessor control, high-quality components, and advanced software design to flawlessly adapt the auxiliary input function to each vehicle's radio.

### The SoundGate AUXMSTHD2V3 works in these applications:

Acura		Honda	
1997	CL 3.0/3.2	1992-1997	Accord
1997-1999	CL 2.2/2.3	1992-1997	Civic
1992-1997	Integra	1995-1997	Odyssey
1992-1995	Legend	1992-1997	Prelude
1992-2001	NSX		
1997-1998	RL 3.5		
1996-1997	TL 2.5/3.2		
1992-1996	Vigor		

ONLY for vehicles equipped with CD-changer-ready radios.

## Be Sure To Ask Your Autosound Specialist About These Other Exciting SoundGate Products...

- Auxiliary Input Interfaces and Docking Stations which allow you to input the audio from MP3, DVD/Video, Satellite Radio, and more to OEM and aftermarket car audio systems
- High-performance Radio Replacement Interfaces for seamlessly integrating new receivers or CD players into OEM audio systems
- Competition-Grade Interfaces for adding amplifiers
- Remote Audio Control Interfaces that let you control aftermarket receivers and CD players from your factory rear seat, or steering-wheel-mounted audio controls.
- And many others!

## Simple-fi™

Copyright© 2004-2007 SoundGate®. All Rights Reserved. SoundGate® is a registered trademark of Stillwater Designs, Inc. All other trademarks are the property of their respective owners.

Rev 20070813

# Installation Instructions

---

## Preliminary:

- A. Turn the ignition key of the car to the “Off” position.
- B. Make sure the car’s factory radio is turned to the “Off” position.

### **Step 1** Gain access to the interfacing location for your AUXMSTHD2V3.

A. You will be connecting the SoundGate AUXMSTHD2V3 at the rear of the radio. Consult a factory service manual for exact disassembly instructions if you are unsure of the procedure. Pay close attention to any warnings regarding working in or around air bags. Gain access to this location.

### **Step 2** Mount the AUXMSTHD2V3 and connect cables.

- A. Mount the AUXMSTHD2V3 at the desired location.
- B. Securely run the cable supplied with the AUXMSTHD2V3 from the AUXMSTHD2V3 to the rear of the radio.
- C. Plug the auxiliary device(s) into the AUXMSTHD2V3’s RCA cable inputs.

### **Step 3** Test the operation of AUXMSTHD2V3.

- Turn the auxiliary device on and place the radio into the “CD Changer” mode. If your auxiliary device is turned on, you should hear the audio from it at this time.
- B. Replace any panels that you removed for access, and your installation is complete!

## Operational Notes

*for listening to your new Auxiliary device...*

**IMPORTANT: Driver distraction (paying attention to your driving) is an important issue. We recommend controlling your auxiliary device only when the car is stationary and parked.**

1. Your auxiliary device is controlled from the device itself.
2. Enter ‘CD Changer’ mode by pressing the radio’s ‘CD’ button, or using the ‘Mode’ button to switch to CD Changer mode.
3. Pushing the “random” “scan” or “repeat” button **twice** switches between Aux Input 1 and Aux input 2.
4. When in Aux Input mode, the radio display will show “Disc1” for Aux input #1, or “Disc2” for Aux input #2.
5. To exit the Aux mode, simply source to AM/FM, or internal CD.

# Installation Instructions

---

## Preliminary:

- A. Turn the ignition key of the car to the “Off” position.
- B. Make sure the car’s factory radio is turned to the “Off” position.

### **Step 1** Gain access to the interfacing location for your AUXMSTHD2V3.

A. You will be connecting the SoundGate AUXMSTHD2V3 at the rear of the radio. Consult a factory service manual for exact disassembly instructions if you are unsure of the procedure. Pay close attention to any warnings regarding working in or around air bags. Gain access to this location.

### **Step 2** Mount the AUXMSTHD2V3 and connect cables.

- A. Mount the AUXMSTHD2V3 at the desired location.
- B. Securely run the cable supplied with the AUXMSTHD2V3 from the AUXMSTHD2V3 to the rear of the radio.
- C. Plug the auxiliary device(s) into the AUXMSTHD2V3’s RCA cable inputs.

### **Step 3** Test the operation of AUXMSTHD2V3.

- Turn the auxiliary device on and place the radio into the “CD Changer” mode. If your auxiliary device is turned on, you should hear the audio from it at this time.
- B. Replace any panels that you removed for access, and your installation is complete!

## Operational Notes

*for listening to your new Auxiliary device...*

**IMPORTANT: Driver distraction (paying attention to your driving) is an important issue. We recommend controlling your auxiliary device only when the car is stationary and parked.**

1. Your auxiliary device is controlled from the device itself.
2. Enter ‘CD Changer’ mode by pressing the radio’s ‘CD’ button, or using the ‘Mode’ button to switch to CD Changer mode.
3. Pushing the “random” “scan” or “repeat” button **twice** switches between Aux Input 1 and Aux input 2.
4. When in Aux Input mode, the radio display will show “Disc1” for Aux input #1, or “Disc2” for Aux input #2.
5. To exit the Aux mode, simply source to AM/FM, or internal CD.